

REMARKS

This Preliminary Amendment cancels, without prejudice, claims 1 to 9 in the underlying PCT Application No. PCT/DE03/03920 and adds new claims 10 to 21. The new claims, inter alia, conform the claims to United States Patent and Trademark Office rules and does not add any new matter to the application.

In accordance with 37 C.F.R. § 1.125(b), the Substitute Specification (including the Abstract) contains no new matter. The amendments reflected in the Substitute Specification (including Abstract) are to conform the Specification and Abstract to United States Patent and Trademark Office rules or to correct informalities. As required by 37 C.F.R. §§ 1.121(b)(3)(ii) and 1.125(c), a Marked-Up Version of the Substitute Specification comparing the Specification of record and the Substitute Specification also accompanies this Preliminary Amendment. Approval and entry of the Substitute Specification (including Abstract) are respectfully requested.

The underlying PCT Application No. PCT/DE03/03920 includes an International Search Report, dated April 20, 2004, a copy of which is included. The Search Report includes a list of documents that were considered by the Examiner in the underlying PCT application.


It is respectfully submitted that the subject matter of the present application is new, non-obvious and useful. Prompt consideration and allowance of the application are respectfully requested.

Respectfully submitted,

KENYON & KENYON

Dated: June 10, 2005

By:



Richard L. Mayer
Reg. No. 22,490
One Broadway
New York, New York 10004
(212) 425-7200
CUSTOMER NO. 26646

RM
42,184

FRICTION-WELDING DEVICE

FIELD OF THE INVENTION

The present invention relates to a friction-welding device for the integral joining of components ~~according to the generic part of Claim 1.~~

5

BACKGROUND INFORMATION

~~Friction welding~~ **Certain friction-welding** devices are ~~known in widely differing designs~~ **conventional**. One distinguishing criterion is the utilized kinematical principle. In the case at hand, devices are involved in which one of two components to be joined is held statically, the other is moved in an oscillating manner, i.e., periodically moved back and forth, and is pressed against the static component in the process. The periodic movement occurs parallel to the provided welding surfaces and is generated by a so-called oscillator. The pressing occurs perpendicular to the welding surfaces with the aid of a suitable compression device. Due to the high compression and friction forces, the usually smaller, moved component is retained in a sturdy cartridge that leaves only the welding zone accessible in most cases. The oscillatory movement may be implemented on a straight and/or curved path, for instance on a portion of a circular arc. In the straight-line variant, the designation "linear friction welding", abbreviated LFW, is often used. In view of the high dynamic stresses, all elements of a friction-welding device must be designed as especially robust and dimensionally stable elements which are free from play, which applies especially when larger components made of high-strength metals are welded. Also important are precise, reproducible and variable friction and compression movements with high positioning accuracy at the end of the dynamic friction process. All of these criteria, after years of development, have had the

result that mechanical and hydraulic variants as well as combinations of the two have become accepted for the direct generation of the required forces and motions. It is understood that the corresponding drives also include
5 electromotors, electronic open-loop and closed-loop controls, i.e., electrical and electronic elements.

The European patent Published Patent Application No. 0 513 669 B1 ~~protects~~ describes a friction-welding method for the
10 blading of a blade carrier for turbo engines together with the required device and device elements. The actual implementation of this friction-welding device operates with the aid of an electromotorically driven, mechanical oscillator according to an eccentric principle, as well as with an
15 electro-hydraulic, pressurized hydraulic compression device.

In mechanical oscillators the maximum movement frequency is limited to values below 100 Hertz (Hz). In hydraulic oscillators the maximum frequency is above 100 Hz but still
20 below 150 Hz. According to the equation power - force x velocity, the friction power is proportional to the friction force, the movement amplitude and the movement frequency. The friction force results from the normal force and the coefficient of friction. At a predefined amplitude,
25 predefined frequency (cf. above maximum values) and predefined coefficient of friction, the friction power can be increased or influenced only via the normal force/pressure force. At a predefined friction power, the relative low frequencies of the mechanical and hydraulic oscillators result in correspondingly
30 high contact pressures that have to be generated by the compression device. High forces require mechanically especially robust and massive, i.e., heavy, components for the friction-welding device.

SUMMARY

~~In view of the known approaches and their disadvantages, it is the objective~~ An example embodiment of the present invention ~~to~~ may provide a friction-welding device for the integral
5 joining of components having periodic movement of one component, which ~~yields~~ may yield geometrically more precise integral components as a result of more precise and better reproducible function, and which ~~allows~~ may allow the
10 manufacture of more filigreed constructions due to higher movement frequencies and lower friction power, lighter and smaller, space-saving device elements being utilizable in the welding area.

~~This object is attained by the features characterized in Claim 1, in connection with the generic features in its first part.~~
15 According to an example embodiment of the present invention, the oscillator ~~includes~~ may include two or a higher, even number of piezoactuators, which are arranged in pairs at least approximately on a line of application. The piezoactuators
20 exert compressive forces from opposite sides on the cartridge having the moved component, so that a defined prestressing is able to be realized, and the periodic friction movement occurs practically without play. Via the electric voltage control/regulation of the piezoactuators with the possibility
25 of acting on each actuator individually, it is possible to select the mechanical prestressing of the cartridge, the movement frequency, the movement amplitude, and the zero position of the movement, including the final position at the end of the welding operation, very precisely and in a
30 reproducible manner. The requirement of complicated refinishing to compensate for geometrical inaccuracies of the welded unit, for instance by NC milling, ~~is~~ may thereby be considerably reduced or eliminated. Due to the lower frictional forces, a smaller and lighter cartridge etc., it is
35 also possible to use friction welding to produce and repair

filigreed, mechanically sensitive blisks (bladed disks) with narrowly positioned blades. In the process, the hubs/disks of the rotors are may be able to be optimally adapted to the operating loads and for the most part be fully finished, so that they ~~will~~ may no longer have to be provided in oversize or with considerable allowances in view of the friction-welding loads, such allowances having to be removed again later on.

10 ~~The dependent claims characterize preferred developments of the friction-welding device according to the main claim.~~

Hereinafter, Example embodiments of the present invention ~~is~~ are explained in greater detail below with reference to the figure appended Figures. ~~In a highly simplified representation that is not to scale, the figures show:~~

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 ~~An~~ illustrates the axial detail of a blade carrier having a blade to be affixed thereon[[:]].

Fig. 2 ~~The~~ illustrates the detail ~~according to~~ illustrated in Figure 1, supplemented by a friction-welding device[[:]].

25 Fig. 3 ~~A~~ illustrates the radial detail of the blade carrier, the blade and the friction-welding device ~~according to~~ illustrated in Figure 2[[:]].

Fig. 4 ~~A~~ illustrates the tangential detail of a blade carrier, a blade and a friction-welding device having four pairs of actuators[[:]].

Fig. 5 ~~A~~ illustrates the detail of a piezoactuator having a flat spring arrangement; ~~and~~.

Fig. 6 ~~An~~ illustrates an arrangement of piezo elements.

DETAILED DESCRIPTION

Figure 1, in an axial view, ~~shows~~ illustrates a portion of a
5 blade carrier 4 intended for a rotor of a turbo engine on
which a blade 3 is to be affixed by friction welding. The
oscillating friction movement is to occur transversely to the
longitudinal center axis of blade carrier 4, which is
~~symbolized~~ indicated by a horizontal double arrow for friction
10 force F_r . Only blade 3 is moved in the process; ~~blade.~~ Blade
carrier 4 is held statically. Welding surfaces 5, 6 are
pressed against each other by a compression force F_s directed
perpendicular to the surfaces, compression force F_s being
introduced into welding zone 7 via moved blade 3. The force
15 arrow pointing toward the blade tip from above is irrelevant
for the actual type of force application into blade 3. To be
preferred, ~~certainly~~ for example, is a force application
producing an even loading, if possible, of a large portion of
the blade surface by a frictionally engaged or a keyed
20 connection.

In addition to components 3, 4 to be friction-welded, Figure 2
~~shows~~ illustrates a friction-welding device 1 according to an
example embodiment of the present invention. For better
25 understanding, Figure 3 should be ~~consulted~~ referred to as
well. To transmit the considerable forces, blade 3 is
virtually completely encased in a mechanically sturdy
cartridge 11, ~~preferably~~ e.g., made of steel or hard metal,
the inner contour of cartridge 11 being adapted to the blade
30 contour in ~~the~~ a best-possible manner. Cartridge 11 ~~is made~~
~~up of~~ includes two or more parts which are screwed together
and have separating lines that are adapted to the blade
geometry. In addition to cartridge 11, oscillator 8, which
generates a defined, periodic friction movement parallel to
35 welding surfaces 5, 6, and compression device 10, which

produces a defined compression force and feed movement, are ~~essential elements~~ components of friction-welding device 1. In the present example embodiment, both oscillator 8 and compression device 10 operate according to the piezoelectrical principle, i.e., on the basis of linear deformation of the piezoelements caused by electric direct voltage. ~~Shown~~ Illustrated in Figure 1 are two horizontal piezoactuators 12, 13 of oscillator 8, which ~~lie~~ are on a line of application and engage with cartridge 11 from the left and right, as well as a piezoactuator 16 of compression device 10, which engages with cartridge 11 vertically from above. The force-transmission points between the piezoactuators and cartridge 11 ~~will~~ usually may have one or more degrees of freedom, depending on the relative movement, for instance for translatory displacements and/or swiveling motions. Slide bearings and/or roller bearings may be used in this context. In the case at hand, for instance, a pivoting joint with a degree of freedom may be arranged between piezoactuator 16 and cartridge 11. The implementation of the force-transmission points ~~is part of~~ the may be conventional expert knowledge and not a direct subject of the present invention. The drawn-in double arrows indicate a synchronous, equidirectional motion of piezoactuators 12 and 13.

~~The principle of the present invention becomes~~ Aspects hereof become even more apparent through with reference to Figure 3. This radial detail of blade carrier 4 and blade 3 ~~shows~~ indicates the blade profile encased by cartridge 11 and the separating lines of cartridge 11 adapted thereto.

Longitudinal center axis X of the blade carrier, i.e., its later axis of rotation, ~~runs~~ extends vertically in this view. It ~~is~~ should be understood that, in a new blading of blade carrier 4, a multitude of blades 3 positioned in close proximity to one another must be affixed at the circumference, only one of which is ~~shown here~~ illustrated for reasons of

clarity. As a result, cartridge 11 ~~must~~ may have to be designed arranged such that there is room for it between already installed blades. This is the explanation for the offset form of the cartridge ~~shown in simplified form~~

5 illustrated. In the case at hand, oscillator 8 has four piezoactuators 12 to 15, which are arranged in pairs on a line of application and are situated transversely to longitudinal center axis X. It should be noted that the piezoactuators may have lengths of several meters due to the required oscillation
10 amplitudes of several millimeters, a multitude of piezoelements being geometrically connected in series, i.e., are arranged one after the other. Therefore, it is

~~advantageous~~ possible to arrange the long piezoactuators 12 to 15 in the manner ~~shown~~ illustrated, in pairs, axially in front

15 and behind the bladed, or to be bladed, blade carrier 4. It should be noted that friction-welding device 1 may be used both for the production of new parts and for repair purposes (repair), i.e., for the replacement of individual or several blades. The two front piezoactuators 12, 13 are synchronously
20 controlled ~~in such a manner~~ that they may always rest against cartridge 11 under compressive stress. The same applies to the two rear piezoactuators 14 and 15. Also, it ~~will most~~ may be likely ~~be the case~~ that the front actuator pair is operated at the same frequency as the rear actuator pair. Given an in-

25 phase condition and identical amplitude of the front and rear actuator pair, blade 3 executes a straight oscillating motion. However, there are also the options of operating an actuator pair at different amplitude and/or with a phase shift relative to the other, yet at the same frequency. For blade 3 that

30 means that combinations of translatory motions and swiveling motions or pure swiveling motions about variable pivotal points are possible. In this context, reference is made to the straight and the curved double arrow above blade 3. This

may require ~~requires~~ a correspondingly flexible connection of
35 piezoactuators 12 to 15 to cartridge 11. Using locally

different forms of movement and different amplitudes, the introduced friction energy may be varied across the welding surfaces, for instance, less friction energy in thin blade regions than in thick regions, so that an even temperature distribution and, ultimately, a better welding result may be achieved.

Figure 4 ~~shows~~ illustrates a detail of blade carrier 4 with blade 3 in the circumferential direction/tangential direction, longitudinal center axis X of blade carrier 4 extending vertically and to the right next to the actual representation. Friction-welding device 2 utilized here differs from the above-described friction-welding device 1 in that its oscillator 9 includes four pairs of piezoactuators, i.e., eight piezoactuators, the representation showing only the four piezoactuators 17 to 20, which are arranged in front of cartridge 11 in the view. Relative to longitudinal center axis X, the effective plane of piezoactuators 17, 18 ~~lies~~ is at a greater radial height H2 than the effective plane of piezoactuators 19, 20, which ~~lies~~ is at radial height H1. ~~During friction-welding experiments it has become apparent that blades~~ Blades may exhibit a slight, undesired tilt in the circumferential direction after welding despite precise radial alignment in the cartridge. Utilizing the illustrated, height-offset actuator pairs ~~makes~~ may make it possible to adjust a selective small, oppositely-directed tilt of cartridge 11 and blade 3 in the circumferential direction during the welding operation, for instance by geometric shifting of the zero point of the higher actuator pairs relative to the lower actuator pairs, so that the exact desired blade orientation results at the end of the welding operation. Compression device 10 having piezoactuator 16 may have the same ~~design~~ arrangement as in the previous figures.

The movement amplitudes of piezoactuators relative to the actuator length are in the per mill range. To reduce the actuator lengths at predefined amplitudes, the actuator amplitudes may be mechanically increased, different gear mechanisms being possible. To this end, Figure 5 ~~shows~~ illustrates a flat-spring arrangement 22 ~~by way of~~ as an example. Two or more flat springs are fixedly clamped into a static base 25 at one end. The other ends of the flat springs are embedded in a displaceable part 24. A pull/pressure element connected to a piezoactuator 21 engages with the flat springs in the region between base 25 and part 24. By elastic deformation of the flat springs, part 24 is moved at a greater amplitude and the same frequency in relation to the pull/pressure element. By moving the pull/pressure element to base 25, it ~~is~~ may be possible to increase the movement amplitude of part 24 while reducing the force exerted by part 24. The movement of part 24 ~~is~~ may not be exactly linear ~~here~~ since a certain swiveling motion is superposed. The kinematics closely resemble a guidance in the form of a parallelogram.

As already mentioned, piezoactuators having amplitudes in the millimeter range have a multitude of piezoelements in a geometrical series connection. It is ~~quite~~ possible that several hundred such piezoelements ~~are~~ may be present. Since conventional piezoelements ~~are~~ may be restricted in cross-section, for instance to the size of a coin, for the generation of great forces it may be required that a plurality of "columns" of piezoelements connected in series ~~must~~ may need to be arranged in parallel and be combined in a, for instance, tubular actuator. Figure 6, in highly simplified form, ~~shows~~ illustrates two "columns" arranged in parallel on a statical base 26. The two columns lead to a displaceable yoke 27 which has the same movement amplitude as each of the columns, at twice the compressive force compared to a single

column. ~~Of course, more~~ More than two collimated "columns" may be combined in one actuator. The geometrical/constructive serial or parallel connection ~~must~~ should not be confused with the electrical circuit of the piezoelements where electrical
5 serial and parallel connections are used as well, the latter especially for the purpose of limiting voltages.

~~Abstract~~

ABSTRACT

A friction-welding device for the integral joining of components, having an oscillator, which generates a periodic movement of a component and a welding surface provided thereon relative to another, static component and a welding surface provided thereon, with directions of movement parallel to the welding surfaces, having a compression device which presses the welding surfaces together, and a cartridge which accommodates the moved component. The oscillator includes two or a greater, even number of piezoactuators, which are arranged in pairs on a line of application and are able to be prestressed with respect to the cartridge from opposite sides under pressure generation and are able to be moved in a synchronous, oscillating manner together therewith and the component.

~~(Figure 2)~~